

**Fully Supported. Superior Performance. Lower Cost**

## **Sentry LP-Video Servers**



- **4 Video/Audio Channels**
- **Rugged, Compact Design**
- **TV Out Support**
- **IR Remote Control**
- **Remote Access via LAN/TCP/IP**
- **Embedded Linux Technology**
- **4 Alarm Inputs/2 Alarm Outputs**
- **Local Recording via USB HDD**

The Sentry LP-VS Series Video Server offers a scalable solution for multi-site surveillance and control. Offering innovative features uncommon to most video servers such as local control and a TV output, the LP-VS takes video from up to four standard CCTV cameras and processes the video to be optimized for transmission over an IP Network. Controlled via web browser, remote software or IR remote control, video from the LP-VS may also be viewed and/or recorded from a Sentry LP Series Hybrid DVR or LP Series NVR.



Included with all Sentry LP Series Video Servers, NVRs and DVRs, the remote client software is an integrated security management system that provides both local and remote access to live and recorded video and all system settings, under password control. Video from multiple LP products can be viewed and recorded on one remote PC. Remote access via a standard Internet browser is also built-in and provides a simple interface to view live video, control PTZ cameras and capture still images.

**Call Sentry to speak with a Digital Video Security Specialist.**

**1.866.736.8796**

[www.sentry-resellers.com](http://www.sentry-resellers.com) | [www.cctvsentry.com](http://www.cctvsentry.com)

**Fully Supported. Superior Performance. Lower Cost**

**Remote Client Software**



Technical Specifications: LP-VS/04	
Video/Audio Channels	4
Video Compression	Hardware MPEG4 / MJPEG Dual Streaming
Video Streaming	up to 120fps @ 360x240 up 120fps @ 720x240 up to 120fps @ 720x480
Bit Rate	32K - 3 Mbps
Live Display	Real-Time (30fps/camera)
PTZ Control	RS-485
Protocols	<u>Pelco P</u> , <u>Pelco D</u> , <u>Merit Lilin</u> , <u>Visca</u> , <u>Dynacolor</u>
Sensor Inputs	4
Relay Outputs	2
Monitor Output	1 TV Out (RCA)
USB 2.0	2 Ports
Video Storage	USB Hard Drive (optional)
Video Event Trigger	Motion Detection, continuous, sensor events
Power Supply	5V, 3A
Operation Temperature	0°C - 70°C
Dimensions	6.5" x 5.5" x 1.8" (16.7cm x 13.8cm x 4.5cm)
Unit Weight	1.21lbs (550g)

**Call Sentry to speak with a Digital Video Security Specialist.**

**1.866.736.8796**

[www.sentry-resellers.com](http://www.sentry-resellers.com)